

# Pioneer™ Series

**Analytical and Precision Balances** 



# The Best Balance For Basic Weighing!

The OHAUS Pioneer<sup>™</sup> Series of analytical and precision balances are designed for basic routine weighing in a variety of laboratory, industrial and education applications. With the right combination of performance and features, the OHAUS Pioneer offers uncomplicated performance for all your basic weighing needs.

#### **Standard Features Include:**

- Easy to Clean Analytical Draftshield Pioneer's draftshield is designed with all glass panels, including three sliding doors. All panels are easy to remove and replace, and together with a stainless steel bottom, make it fast and easy to clean
- **Upfront Level Indicator** Pioneer has been designed with an up-front level indicator, so that users can quickly ensure the balance is level prior to use
- Selectable Environmental Settings Three filter modes and adjustable zero tracking adjust balance sensitivity to environmental disturbances, or application requirements

### Removable Doors Provide Convenient Access and Easy Cleaning

To address the ease of cleaning requirement often expressed by routine users, Pioneer's draftshield has been designed with easy to remove doors and panels. Disassembly takes just seconds and all components including the balance housing can be quickly wiped clean.



Periodic cleaning made easy helps avoid sample contamination and extends product life. In addition, a standard in-use cover provides added protection against accidental spillage and helps minimize the chance of damage to the display and keypad.



Should breakage occur, each replacement door or panel can be installed in seconds. A standard in-use cover provides added protection against accidental spillage.

# **Upfront Level Indicator Ensures Accuracy**

The Pioneer has been designed with an up-front level indicator, eliminating the need to look behind the balance during the leveling process. A quick glance at the up-front level indicator helps you ensure that the balance is level prior to each use.





# Selectable Environmental Settings For Working in Practically Any Condition

To help adapt the balance to real life working conditions, Pioneer is designed with selectable environmental settings. When working in harsh environments, the balance can be adjusted to compensate for vibrations and other disturbances. Conversely, the balance can be adjusted for working in slow filling applications where sensitivity is a must.

#### **Specifications**

| Model                           | PA64   | PA114     | PA214      | PA153      | PA313       | PA512  | PA1502  | PA3102    | PA4101  |
|---------------------------------|--|-----------|------------|------------|-------------|--|---|-----------|---------|
| Capacity (g)                    | 65   | 110       | 210        | 150        | 310         | 510  | 1500  | 3100      | 4100    |
| Readability d (g)               | 0.1 mg   |           |            | 0.001      |             | 0.01   |   |           | 0.1     |
| Repeatability (Std Dev)         | 0.1 mg   |           |            | 1 mg       |             | 10 mg  |   |           | 100 mg  |
| Linearity                       | 0.2 mg   |           | 0.3 mg     | 2 mg       |             | 20 mg  |   |           | 100 mg  |
| Application Modes               | Weighing, Parts Counting, Percent  |           |            |            |             |  |   |           |         |
| Weighing Units                  | mg, g, ct, oz, dwt, tical, tola, mommes, baht, grain, mesghal,<br>Newton, ozt, teals                         |           |            |            |             | g, lb, ct, oz, dwt, tical,<br>tola, mommes, baht,<br>grain, mesghal, Newton,<br>ozt, teals | g, kg, lb, ct, oz, dwt, tical, tola, momme:<br>baht, grain, mesghal, Newton, ozt, teals |           |         |
| Platform Size                   | 3.54 in / 9 cm diameter 4.72   |           |            |            | cm diameter | 7.1 in / 18 cm diameter  |   |           |         |
| Cal Weight-Span                 | 50, 60g  | 50, 100g  | 100, 200g  | 100, 150g  | 200, 300g   | 200, 500g  | 1000, 1500g   | 2, 3kg    | 2, 4kg  |
| Cal Weight-Linearity            | 20 / 50g   | 50 / 100g | 100 / 200g | 100 / 150g | 150 / 300g  | 200 / 500g   | 1000 / 1500g  | 1.5 / 3kg | 2 / 4kg |
| Taring Time                     | 1 second   |           |            |            |             |  |   |           |         |
| Stabilization Time              | 3 seconds  |           |            |            |             |  |   |           |         |
| Draftshield                     | 7.3 in / 18.5 cm inside height   |           |            |            |             | None   |   |           |         |
| Operating Conditions            | 50° F / 10° C to 104° F / 40° C at 10% to 80% relative humidity, non-condensing, up to 4000m above sea level |           |            |            |             |  |   |           |         |
| Storage Temperature             | -40° F / -40° C to 158° F / 70° C at 10% to 80% relative humidity, non-condensing.                           |           |            |            |             |  |   |           |         |
| Gross Weight                    | 10.0 lb / 4.5 kg   |           |            |            |             | 7.3 lb / 3.3 kg  |   |           |         |
| Shipping Weight                 | 15.2 lb / 6.9 kg   |           |            |            |             | 11.8 lb / 5.4 kg   |   |           |         |
| Balance Dimensions<br>W x H x D | 7.7 x 11.3 x 12.6 in / 19.6 x 28.7 x 32 cm   |           |            |            |             | 7.7 x 3.6 x 12.6 in / 19.6 x 9.2 x 32 cm   |   |           |         |
| Carton Dimensions<br>L x W x H  | 19.5 x 15.5 x 20.6 in / 49.5 x 39.5 x 52.2 cm  |           |            |            |             | 19.5 x 15.5 x 12.8 in / 49.5 x 39.5 x 32.7 cm  |   |           |         |

#### **Outline Dimensions**

