Strain Reliefs





Seal electrical connections against dust and dirt, oil, water or other atmosphere containing moisture with strain reliefs from Totalcomp

- 1/2" hub size fpr 7/8"hole
- Aluminum with rubber bushing
- "O" ring gasket on outside of box for watertight fit
- Lock nut holds from inside

email: sales@totalcomp.com

Specifications

Strain reliefs



Totalcomp
CG strain relief

email: sales@totalcomp.com

Totalcomp CG strain reliefs are used to connect load cell cables to summing junction boxes or instrument enclosures.

CG strain reliefs contain a knurled collar that compresses the bushing around the cable for a watertight fit and relief of strain on cable inside the box..

Part Number CG-1250	Cable dia 0-125"-0.187"	Length 1.5"	Diameter 0.875"	Weight 0.07 lb	Stock 625
CG-1850	0.187"-0.312"	1.5"	0.875"	0.07 lb	626
CG-3150	0.312"-0.437"	1.5"	0.875"	0.07 lb	627

Totalcomp Limited Warranty

Totalcomp warrants this product to be free of defects in materials and/or workmanship and suitable for the purpose intended as outlined in this sheet. This warranty is effective and shall cover the purchaser for one year from the date of shipment from our plant. If this product is found to be defective by our inspection in accordance with the above listed criteria, we will replace or repair it at our expense. For warranty service, please obtain a return authorization number from us and return the item, shipping prepaid, with a written description of the problem. We will respond promptly with the results of our evaluation.

