TRWS

DIGITAL INDICATOR



Totalcomp
TRWS

Stainless Steel, Waterproof Digital Indicator from Totalcomp

- ✓ ***NTEP approved for 6,000 divisions***
- ✓ ***IP65 watertight***
- ✓ ***6 mechanical switch keys***
- ✓ ***Stainless steel housing***
- ✓ ***Backlit LCD display with 22mm digits***
- ✓ ***RS-232 can connect to a mini printer, label printer or computer***

Totalcomp® ***Scales & Components***

99 Reagent Lane • Fair Lawn, New Jersey 07410
Fax: 201-797-2287 • Toll Free Fax: 888-797-2288 • Phone: 201-797-2718 • Toll Free Phone: 800-631-0347
Email: sales@totalcomp.com • Website: www.totalcomp.com

TOTALCOMP TRWS DIGITAL INDICATOR

The Totalcomp TRWS Stainless Steel, Waterproof, Digital Indicator is compact and easy to setup. TRWS is capable of powering up to 4-350 load cells, this simple device can handle multitude of functions. Applications for Check Weighing, Accumulation, Over/Under and Animal Weighing. A full RS-232 port can transmit data on demand or continuously to match the input requirements of a wide variety of peripheral devices including miniprinters, label printers and computers. Size: 4.63"H x 7.75"W x 3.25"D. NTEP 13-091 III 6,000 div

Part Number	Weight
TRWS Indicator	7 lb

Load Cell Excitation
±5 VDC, 150 ma

Load Cell Current
Drives up to four 350 Ω Load Cells

Analog Signal Input Range
0 to 15 mV
0.5 mV/div

Conversion Rate
Update max 60 times per sec
1, 2, 5, 10, 20, 50 div

Accuracy
0.01% full scale

Output
RS232

Key Functions
Units, Print, G/N, Tare, Zero, On/Off

Annunciators
lb, kg, g, oz, tj, hj, mt, hi, ok, lo, %, Peak, Battery, Hold, Stable, Auto, Animal, Zero, Tare, Net, Gross

Display
6 digit 22mm LCD with backlight

Power
AC adapter (9V/800mA)
Ni-MH batteries (1.2V/1200mAhx6)

Max. Divisions
30,000d

ADC
Sigma Delta

ADC Update
≤1/10 second

Operating Temperature
0º C~ + 40º C

Gross Weight
2 lbs

TOTALCOMP LIMITED WARRANTY

Totalcomp warrants this product to be free of defects in materials and/or workmanship and suitable for the purpose(s) intended as outlined on this sheet. This warranty is effective and shall cover the purchaser for one year from the date of shipment from our plant. If this product is found to be defective by our inspection in accordance with the above listed criteria, we will replace or repair it at our expense. For warranty service, please obtain a return authorization number from us and return the item, shipping prepaid, with a written description of the problem. We will respond promptly with the results of our evaluation.

Totalcomp®
Scales & Components

99 Reagent Lane
Fair Lawn, NJ 07410
Fax (201) 797-2287
Toll Free Fax (888) 797-2288
Phone (201) 797-2718
Toll Free Phone (800) 631-0347
Email sales@totalcomp.com
Website www.totalcomp.com