

Electronic Jewelry Balances

Ohaus Portable Carat Scale Order Item # JS10



Specifications	
Capacity:	10g (50ct)
Readability:	0.002 g (0.01 ct)
Weighing units:	ct, g, oz t, dwt, grains, tael(3), pc, oz
Weighing modes:	Parts Counting
Repeatibility (Std. Dev.) (g):	0.002
Linearity (g):	± 0.002
Tare range:	To capacity by subtraction
Over Range Capacity:	103%
Stabilization time (seconds):	3
Operating Temperature Range:	50° to 104°F / 10° to 40°C
Operating Humidity Range:	10% to 85% RH
Power Requirements:	AC Adapter: 100V, 120V, 220V, 240V AC 50/60 Hz or 9V battery
Display (in/cm):	0.7/1.8
Display type:	LCD
Pan size (in/cm):	3/7.6
Dimensions WxHxD (in/cm):	6.75 x 2.4 x 8.25 17.1 x 6.2 x 21
Net Wt. (lb/kg):	1.8/0.8
Shipping Wt. (lb/kg):	3.5 / 1.6
Auto shut-off:	Programmable on/off
Calibration:	Digital from keypad
Diamond & Jewelry:	Available only through authorized Ohaus jewelry dealers.
Scoop size (L x W x D) (in/cm):	1.5 x 1.2 x 0.4/3.7 x 3.0 x 0.9
Shipping dimensions (WxDxH) (in/cm):	7.0 x 9.3 x 2.3 / 17.8 x 23.5 x 5.7

Electronic Jewelry Balances



Ohaus Portable Precious Metals Scale Order Item # JS500

Specifications	
Weighing units:	ct, g, oz t, dwt, pc, oz
Weighing modes:	Parts Counting
Repeatability (Std. Dev.) (g):	0.1
Linearity (g):	± 0.1
Tare range:	To capacity by subtraction
Over Range Capacity:	103%
Stabilization time (seconds):	3
Operating Temperature Range:	50° to 104°F / 10° to 40°C
Operating Humidity Range:	10% to 85% RH
Power Requirements:	AC Adapter: 100V, 120V, 220V, 240V AC 50/60 Hz or 9V battery
Display (in/cm):	0.7/1.8
Display type:	LCD
Pan size (in/cm):	5 x 5.75/12.7 x 14.6
Dimensions WxHxD (in/cm):	6.75 x 2.4 x 8.25 17.1 x 6.2 x 21
Net Wt. (lb/kg):	1.8/0.8
Shipping Wt. (lb/kg):	3.5 / 1.6
Auto shut-off:	Programmable on/off
Calibration:	Digital from keypad
Diamond & Jewelry:	Available only through authorized Ohaus jewelry dealers.
Shipping dimensions (WxDxH) (in/cm):	10.5 x 12.0 x 5.0 / 26.7 x 30.5 x 12.7