

PPC-300-II Series Portion Control Scales

- Checkweighing, grading, basic weighing, and tare functions
- Pound, kilogram, ounce, pound-ounce
- Programmable auto-off



MODEL	PPC-300-II-4.4	PPC-300-II-10	PPC-300-II-22	PPC-300-II-44	PPC-300-II-60
Capacity	4.4lb x 0.002lb 80oz x 0.05oz 2kg x 0.001kg 5lb x 0.05oz*	10lb x 0.005lb 160oz x 0.1oz 4kg x 0.002kg 10lb x 0.1oz*	22lb x 0.01lb 352oz x 0.2oz 10kg x 0.005kg 22lb x 0.2oz*	44lb x 0.02lb 704oz x 0.5oz 20kg x 0.01kg 44lb x 0.5oz*	60lb x 0.02lb 1056oz x 0.5oz 30kg x 0.01kg 66lb x 0.5oz*
Weighing System	Strain gauge load cell				
Certificate of Conformance	22-002 (US) AM-6204 (Canada)				
Platform	9.1in x 8in (232mm x 202mm), stainless steel, removable				
Display	5-digit, 7-segment LCD				
Character Size	0.5in x 1.2in (13mm x 30mm)				
Power	"D" size batteries (qty. 4) or AC adapter (included)				
Battery Life	3000 hours of continuous use				
Housing Material	ABS with stainless-steel platform				
Operating Temperatures	14°F ~ 104°F (-10°C ~ 40°C)				
Function	Basic weighing, checkweighing, grading, fixed, tare				

*Combined units, such as pound-ounce, are not legal for trade.

Dimensions

