

# SRP-300



Shown here with optional roller ball top



\* CLASS III 3,000 div  
CC #95-034

The SRP-300 multi-purpose NTEP approved bench scale is designed for use in today's rugged industrial applications. The SRP-300 is constructed utilizing a heavy-duty carbon steel understructure allowing for maximum overload protection, a sealed aluminum load cell, and a heavy gauge stainless steel weigh pan. Each SRP-300 includes six feet of cable from the base to the indicator. An 18" or 30" stainless steel column is available as an option. The scale can transmit on demand or continuously in several popular UPS manifest data protocols.



# SRP-300

## MILD STEEL BENCH SCALE

### STANDARD FEATURES & BENEFITS

- \* **NTEP APPROVED LEGAL FOR TRADE**
- \* **EMULATES SEVERAL UPS MANIFEST PROTOCOLS - EASY SETUP**

- \* **SERIAL COMMUNICATION PORT**

Communications with peripherals is made simple utilizing the full Duplex RS-232 serial communication port.

- \* **SIMPLE OPERATION:**

The 5 button keyboard provides a simple Zero, lb/kg Net/Gross, Pushbutton Tare, and Print key.

- \* **RUGGED CARBON STEEL CONSTRUCTION:**

Heavy-duty carbon steel construction for rugged environments. The sealed load cell is coated for surface protection and secured from overload by five mechanical stops.

- \* **HIGH RESOLUTION AND ACCURACY:**

Standard resolution is 3,000 divisions.

- \* **BRIGHT BLUE/GREEN VFD**

A high-intensity VFD allows easy, non-fatiguing and accurate viewing of weight data

### Other Features

- ▷ **Adjustable Swivel Display For Optional 18" or 30" column:**  
Allows indicator alignment for best viewing angle.
- ▷ **Print Format:** Contains Gross Weight, Tare, Net
- ▷ **Digital Keyboard Calibration**
- ▷ **1 Year Warranty**
- ▷ **Sealed Aluminum Load Cell**
- ▷ **Mechanical Overload Stops**
- ▷ **Stainless Steel Shroud**

### Options

- 18" stainless steel column and indicator bracket
- 30" stainless steel column and indicator bracket
- Stainless Steel Ball Top

### Specifications:

<b>CONSTRUCTION:</b>	
<b>Indicator Housing:</b>	Black ABS steel backplate
<b>Sub-Platform:</b>	ABS & Metal
<b>Platter:</b>	Stainless Steel
<b>Feet:</b>	Non-skid Hard Rubber
<b>DISPLAY:</b>	7-Digit Vacuum Fluorescent Display
<b>KEYPAD:</b>	5-Key Tactile Keypad
<b>OVER CAPACITY ANNUNCIATION:</b>	103% of Full Scale Capacity
<b>SERIAL PORT:</b>	Full Duplex, RS-232 Female DSUB9
<b>OPERATING TEMP RANGE:</b>	32°F to 100°F 0°C to 40°C
<b>MAIN POWER SOURCE:</b>	AC Adapter, 12VDC, 650 mA, included
<b>WEIGHT:</b>	
<b>Net Weight:</b>	43 lb
<b>Shipping Weight:</b>	49 lb
<b>OPTION:</b>	NMC-1 Null Modem Cable



### CAPACITY & SIZE

300lb x .1 lb	18" x 18"
---------------	-----------



**TRANSCCELL TECHNOLOGY, INC.**

975 Deerfield Pkwy, Buffalo Grove, IL 60089  
Tel (847) 419-9180 Fax (847) 419-1515

**(800) 503-9180**

www.transcell.net

Specifications and features subject to change without notice.