



More information on the website
radwag.com/en/info,w1,Q67

WTC 200 Precision Balance



Functions



Plus/Minus Control



Percent Weighing



Parts counting



Peak hold



GLP Procedures



ALIBI Memory

Datasheet

Metrological parameters

Maximum capacity [Max]	200 g
Readability [d]	0,001 g
Tare range	-200 g
Repeatability	0,002 g
Linearity	±0,004 g
Stabilization time	2 s
Adjustment	external

Physical parameters

Levelling system	manual
------------------	--------

Physical parameters	
Display	LCD (backlit)
Weighing pan dimensions	ø100 mm
Packaging dimensions	330×230×140 mm
Net weight	1,3 kg
Gross weight	2 kg
Protection class	IP 43
Communication interface	
Communication interface	RS232, USB-A, USB-B
Electrical parameters	
Power supply	100-240 V AC 50/60 Hz and battery
Power consumption max.	6 W
Operation time on batteries	15 h (average time)
Environmental conditions	
Operating temperature	+15 ÷ +30 °C

Repeatability is expressed as a standard deviation from 10 weighing cycles.

Stabilization time depends on the ambient conditions and the dynamics of weighing pan loading; specified for FAST profile.



Accessories

Receipt Printer
Cigarette lighter receptacle power supply cables
Displays



RS 232, RS 485 cables
RS 232 cables (scale - EPSON printer)

Software

RAD-KEY
LabVIEW Driver
R-LAB

RW Tool
R Panel
Scales Editor 2.0

Device dimensions



WTC, d = 0.001 g