

SJ Series

Low Profile Digital Scales



Features

- Choice of Units: g, oz, lb-oz, lb
- Large, Removable, Stainless Steel Pan (9" x 7 1/2")
- Fast Response (less than one second)
- Automatic Power Off
- 800 Hour Battery Life
- Easy to Read 1" LCD Display
- Battery Level Indicator
- Full Digital Calibration

Fax-on-Demand
(800) 726-7099, Press 2
Document #1018
www.andweighing.com

A&D
A&D WEIGHING
...Clearly a Better Value



1555 McCandless Drive
Milpitas, CA 95035, USA
Toll Free: (800) 726-7099
Phone: (408) 263-5333
Fax: (408) 263-0119

SJ Series Specifications:

		SJ-1000HS	SJ-2000HS	SJ-5000HS	SJ-12KHS
Capacity	(k)g	1000 g x 0.5 g	2000 g x 1 g	5000 g x 2 g	12 kg x 0.005 kg
	lb	2.2 lb x 0.001 lb	4.4 lb x 0.002 lb	11 lb x 0.005 lb	26 lb x 0.01 lb
	oz	35 oz x 0.02 oz	70 oz x 0.05 oz	176 oz x 0.1 oz	423 oz x 0.2 oz
	lb-oz	2.2 lb x 0.1 oz	4.4 lb x 0.1 oz	11 lb x 0.1 oz	26 lb x 1 oz
Non-linearity		±1 g	±2 g	±5 g	±10 g
Repeatability		1 g	2 g	5 g	10 g
Span Drift		±0.015% / °C TYP (5°C - 35°C / 41°F - 95°F)			
Operating Temp.		-10°C - 40°C / 14°F - 104°F, Less than 85% RH (No condensation)			
Display		25 mm / 0.98 inches, 7 segment liquid crystal display			
Display Update		Approximately 10 times per second			
Power		4 "D" size batteries or AC Adapter			
Battery Life		Approximately 800 hours with alkaline cells at 20°C / 68°F			
Platform Size		230 (W) x 190 (D) mm / 9.05 (W) x 7.48 (D) inches			
Dimensions		265 (W) x 250 (D) x 103 (H) mm 10.4 (W) x 9.8 (D) x 4.1 (H) inches			
Weight		Approximately 1.7 kg / 3.7 lb			
Calibration Weight		1000g ± 0.1 g	2000 g ± 0.2 g	5000 g ± 0.5 g	10 kg ± 1 g
Options		AC Adapter			

Specifications are subject to change without notice.