

SK-WP / SK-WPZ Series

STAINLESS STEEL, WASHDOWN DIGITAL SCALES

Ideal for harsh environment applications, such as food processing, foodservice, chemical and outdoor use

**Resolution
Up to 5,000
divisions!**

**Large 1" LCD
Display**

**Battery Powered
(batteries not included)**



**lb / kg / oz Mode Selection
(varies with model)**

NTEP Approved



NSF Certified



Features

- 2 Year Warranty
- Low Battery Indication with Auto Power Off (5 min.) to preserve battery life
- AC Adapter (optional)
- Large, removable stainless steel pan (9" x 7.5")
- Temperature Compensated
- Full Scale Pushbutton Tare/Zero

SK-WP Series	Metric Mode		Lb Mode	
	Capacity	Resolution	Capacity	Resolution
SK-1000WP	1000 g	0.5 g	2.2 lb	0.001 lb
SK-2000WP	2000 g	1 g	4.4 lb	0.002 lb
SK-5000WP	5000 g	2 g	11 lb	0.005 lb
SK-5001WP	5000g	1g	-	-
SK-10KWP	10 kg	0.005 kg	22 lb	0.01 lb
SK-20KWP	20 kg	0.01 kg	44 lb	0.02 lb

SK-WPZ Series	Metric Mode		Lb Mode		Dec. oz Mode		Fract. oz Mode	
	Capacity	Resolution	Capacity	Resolution	Capacity	Resolution	Capacity	Resolution
SK-2000WPZ	2000 g	1 g	4.4 lb	0.002 lb	4 lb, 6 oz	0.1 oz	4lb, 6oz	1/16 oz
SK-5000WPZ	5000 g	2 g	11 lb	0.005 lb	11 lb	0.1 oz	11 lb	1/8 oz
SK-20KWPZ	20 kg	0.01 kg	44 lb	0.02 lb	44 lb	1 oz	44 lb	1 oz

Fax-on-Demand

(800) 726-7099, Press 2 / (408) 263-2278

Document #1010

www.andweighing.com



1555 McCandless Drive
Milpitas, CA 95035, USA
Toll Free: (800) 726-7099
Phone: (408) 263-5333
Fax: (408) 263-0119

SK-WP / SK-WPZ Series Specifications

	SK-1000WP	SK-2000WP	SK-5000WP	SK-5001WP	SK-10KWP
Grams (g)	1000 x 0.5g	2000 x 1g	5000 x 2g	5000 x 1g	-
Kilogram (kg)	-	-	-	-	10 x 0.005kg
Pounds (lb)	2.2 x 0.001lb	4.4 x 0.002lb	11 x 0.005lb	-	22 x 0.01lb
Linearity	± 1g	± 2g	± 4g	± 2g	± 0.01kg
Repeatability/ Std. Deviation	0.5g	1g	2g	1g	0.005kg

	SK-20KWP	SK-2000WPZ	SK-5000WPZ	SK-20KWPZ
Grams (g)	-	2000 x 1g	5000 x 2g	-
Kilogram (kg)	20 x 0.01kg	-	-	20 x 0.01kg
Pound (lb)	44 x 0.02lb	4.4 x 0.002lb	11 x 0.005lb	44 x 0.02lb
Lb/oz fractional ounce	-	4 lb, 6oz x 1/16 oz	11 lb x 1/8 oz	44 lb x 1 oz
Lb/oz decimal ounce	-	4 lb, 6 oz x 0.1 oz	11 lb x 0.1 oz	44 lb x 1 oz
Linearity	± 0.02kg	± 2g	± 4g	± 0.02kg
Repeatability/ Std Deviation	0.01kg	1g	2g	0.01kg

All Models	
Display	25mm/ 1 inch, 7 segment LCD
Platform Size	232 (W) x 192 (D) mm / 9.1 (W) x 7.5 (D) inches
Dimensions	150 (H) x 266 (W) x 280 (D) mm / 5.75 (H) x 10.5 (W) x 11 (D) inches
Power	6 'D' size batteries (not included) or FV-05 AC adapter (option)
Battery Life	Approx. 600 hours (manganese type), 1200 hours (alkaline at 20° C / 68° F)
Operating Temp.	-10°C~40°C / 14°F~104°F RH less than 85%
Weight	Approx. 2.9 kg. / 6.4 lb

Specifications are subject to change without notice.

Options:

- FV-05 AC Adapter (110VAC) – power transformer is not waterproof
- FV-06 AC Adapter (220VAC) – power transformer is not waterproof

**NTEP APPROVAL CofC#98-086A2
(Except SK-5001WP and WPZ models)**

Fax-on-Demand

(800) 726-7099, Press 2 / (408) 263-2278

Document #1010

www.andweighing.com



1555 McCandless Drive
Milpitas, CA 95035, USA
Toll Free: (800) 726-7099
Phone: (408) 263-5333
Fax: (408) 263-0119