

Touch Screen Indicator

T7-P & S7-SS



ABS and Stainless Steel Touch Screen Indicators

- ✓ **6.75" touch screen display**
- ✓ **Store 9999 product ID**
- ✓ **Built in applications**
- ✓ **Run(16) 350 ohm load cell**
- ✓ **Time / Date Standard**
- ✓ **USB port for Barcode, scanner, software update, data download**



Totalcomp[®] Scales & Components

99 Reagent Lane • Fair Lawn, New Jersey 07410

Fax: 201-797-2287 • Toll Free Fax: 888-797-2288 • Phone: 201-797-2718 • Toll Free Phone: 800-631-0347

Email: sales@totalcomp.com • Website: www.totalcomp.com

T7-P has ABS plastic enclosure. 6.75" touch screen display. **T7-SS has IP65 stainless steel housing.** 6.75" touch screen display. 5 tactile keys for: On/Off, Set up, Home, Tare, Zero. Panel home screen keys for: Class, Take Out, Target, Count, Check, M+, Pre-Tare, Print, Sum. Applications for: Hi/Lo, Unit, Product. Built in applications include: standard weighing, over/under check weighing with bar graph, Take Out, Target, Counting, Class(grading), Hi/Lo applications. Built in Time/Date clock. Indicator has 4 Pre-Tare settings that can be saved and one Pre-Tare setting for custom entry. T7-P and T7-SS can store up to 9999 product ID by product name, barcode, Pre-Tare, unit weight in g/pcs or lb/pcs, Hi.Lo level. If product ID has barcode assigned to it using optional barcode scanner, product ID retrievable for fast access. M+ function will add weighment to memory that is retrievable with Sum and transferred to PC using flash drive or printed on paper and then cleared manually. USB port for plug and play ZoomSun barcode scanner and software upload and data download. T7-P is equipped with 1xRS232 port, 1xRS422, 2x USB port. T7-SS is equipped with 1xRS232 port, 1x USB port.

T7-P Weight 7 lb

T7-SS Weight 8 lb

Options:

ZoomSun USB barcode scanner Weight 2 lb

OS-2130D Argox direct thermal printer Weight 2 lb



ZoomSun USB Barcode Scanner



OS-2130D Argox direct thermal printer

SPECIFICATIONS

LOAD CELL5VDC,
(16)350 ohm load cells

ANALOG INPUT2.5 μ V/div

CONVERSIONInternal count: 1,000,000
External Resolution 6000e

ACCURACY0.01% of full scale

OUTPUTT7-20: RS232, RS422, 2 USB ports
S7-20: RS232, USB port
Cortex Dual Core

KEYS.....ON/OFF, SET UP, HOME, TARE, ZERO

ANNUNCIATORSkg, g, lb, oz, tj, gj, lz

DISPLAY5 digit, 6.75" touch screen display
Display div 1, 2, 5, 10, 20, 50, 100

POWERInternal 6VDC battery and AC adapter included.

SIZET7-20: 9.34"W x 4.25"D x 6.58" H
S7-20: 10.58W" x 3.5"D x 6.58"H

TOTALCOMP LIMITED WARRANTY

Totalcomp warrants this product to be free of defects in materials and/or workmanship and suitable for the purpose(s) intended as outlined on this sheet. This warranty is effective and shall cover the purchaser for one year from the date of shipment from our plant. If this product is found to be defective by our inspection in accordance with the above listed criteria, we will replace or repair it at our expense. For warranty service, please obtain a return authorization number from us and return the item, shipping prepaid, with a written description of the problem. We will respond promptly with the results of our evaluation.



Totalcomp®

Scales & Components

99 Reagent Lane

Fair Lawn, NJ 07410

Fax (201) 797-2287

Toll Free Fax (888) 797-2288

Phone (201) 797-2718

Toll Free Phone (800) 631-0347

Email sales@totalcomp.com

Website www.totalcomp.com