



CLASS III CERTIFICATE
#97-135

CS™ Series

DIGITAL CRANE & TENSION LINK SCALES

ISO 9001
Registered

CS200™ / CS750™ / CS1500™ / CS3000™ / CS5000™ / TL6000™



Infrared remote control is standard on the CS750, CS1500 and CS3000 Crane Scales



Get Tomorrow's Crane Scale Technology Today from Intercomp.

Intercomp offers the industry's most extensive line of crane scales, and can provide your company with a cost-effective solution to virtually every overhead industrial weighing application - ranging from 25 to 600,000 lbs/ 12.5 to 300,000 kg.

Our advanced design, value-packed with the industry's most desired features, makes *Intercomp* the first choice over other electronic units. Ultra high-resolution, A/D conversion delivers unsurpassed accuracy, and digital keypad setup and calibration enhance the ease of operation.

All crane unit electronics are shock-mounted in a weatherproof case and provide maximum protection against moisture, dust and rough usage. Features include a high-visibility digital readout for easy reading of weights and large pushbutton switches for simple, trouble-free operation. All units are supported by a full one-year parts and labor warranty.

For all your overhead industrial weighing needs, look to Intercomp.

Intercomp®
advanced weighing technology . . . by any measure

CS200™


High accuracy, compact digital hanging scale for low capacity applications.

Tremendously compact (weighs only 1.6 lb) and accurate (+/- 0.1% of applied load) for ranges from 25 to 500 lb/12.5 to 250 kg. The unit operates for up to one year on a single standard 9-volt alkaline battery. Supported by a full one-year parts and labor warranty. Perfect for tight budgets.

Specifications

- POWER:** 9V Alkaline or Nicad
- SIZE:** 3.75" (W) x 2" (D) x 6" (H) inches
94 x 50 x 150mm
- WEIGHT:** 1.6 lb / 0.75 kg
- DISPLAY:** 0.5 inch/12mm LCD
- TEMPERATURE RANGE:** -4 to 140°F (-20 to 60°C)
- OVERLOAD:** 200% of capacity
- FEATURE:** Peak Hold
- CONTROLS:** On/Off, Zero and lb/kg

CAPACITY	GRADUATION
25 lb	0.01 lb
12.5 kg	0.01 kg
50 lb	0.02 lb
25 kg	0.01 kg
100 lb	0.05 lb
50 kg	0.02 kg
250 lb	0.10 lb
125 kg	0.05 kg
500 lb	0.20 lb
250 kg	0.10 kg



CS750™

NTEP (300, 500 & 1000 lb.)

High accuracy, compact digital hanging scale for low capacity industrial applications.

Capacities on the CS750 range from 25 to 1,000 lb / 12.5 to 500 kg. Keypad setup and digital calibration enhance ease of operation. The unit utilizes a high-visibility 1 inch / 25 mm LCD digital readout with backlight and will operate for up to one year on six (6) D-cell batteries. Crosby eyehook and bottom swivel hook standard.

Specifications

- CONTROLS**
 - General: Zero, On, Off, Backlight
 - Display: 5 digit, 1 inch/ 25mm liquid crystal display (LCD)
 - Indicators: lb/kg
- ELECTRICAL**
 - Battery Life: 1-year normal use
 - Batteries: Six (6) "D"-size disposable alkaline dry cells or rechargeable nicad cells (Not included)
 - Resolution: 20-bit A/D converter delivers over 1,000,000 internal counts
 - Filtering: 6-pole, 10 hertz low pass
 - Auto Shut-off: Low battery, or after 5 minutes without use
 - Auto-Zero: Satisfies all NIST/OIML requirements
 - Zero: Up to 100% excluding NIST/OIML units


- PERFORMANCE**
 - Speed: 3 Seconds to typical reading
 - Accuracy: +/- 0.1% of reading

- ENVIRONMENTAL**
 - Humidity: 10 to 95% non-condensing
 - Temperature: Operating -4 to 140°F/-20 to 60°C


- PHYSICAL**
 - Nominal Overload: 200% of capacity
 - Maximum Overload: 500% of capacity
 - Dimensions: Control Box - 4.25" x 5" x 8.5"
108 x 127 x 216 mm
Lifting eye to hook - 9.5"/241 mm
 - Enclosure: Extruded aluminum case
 - Weight: 7.5 lb/3.4 kg

Options:

- RS-232 Serial output
- LED display
- Direct 120/ 220 volt power supply



Infrared Remote Control



CAPACITY	GRADUATION
25 lb	0.01 lb
12.5 kg	0.01 kg
50 lb	0.02 lb
25 kg	0.01 kg
100 lb	0.05 lb
50 kg	0.02 kg
*300 lb	0.10 lb
150 kg	0.05 kg
*500 lb	0.20 lb
250 kg	0.10 kg
*1000 lb	0.50 lb
500 kg	0.20 kg

* NTEP approved