



THE READABLE, INTERFACEABLE, DURABLE, AFFORDABLE DISPLAY

READABILITY

The display is clearly readable from 225 feet in pouring rain, bright sun, pitch dark, inside or out, without external support lighting or shielding.

INTERFACEABILITY

The display will interface with any digital indicator, input terminal, or computer that is commercially available.

DURABILITY

The display features light emitting diodes (LED's) which, unlike "liquid crystal" displays, can withstand temperatures ranging from -50° to 120° F. They have no bulbs to burn out or electromechanical shutters to malfunction. The display is NEMA 4X rated, moisture tight encasement.

4 MODELS

The display comes in four models to meet your exacting needs:

- Model S400™—Numerical only, Indoor Display
- Model S400™HI—Numerical only, Outdoor Display
- Model S480™—Alpha/Numeric, Indoor Display
- Model S480™HI—Alpha/Numeric, Outdoor Display

OPTIONS

A Time/Date display option is available with the display. If incorporated, the display will automatically indicate time and date alternately just 4 seconds after the display has been released from your input.

SPECIFICATIONS

Standard Serial: RS-232 to 50 ft. (15.25 meters) or 20mA current loop to 1500 ft. (455 meters) (active or passive) at all standard baud rates from 50 to 9600. Interface cable included, 25 feet (7.62 meters).

Standard Parallel: TTL BCD 199999 Range—Minus line—Motion/Overcapacity Line—"Print" (Strobe) Line. Interface cable included, 25 feet (7.62 meters).

Weight: 8 pounds (3.6 kg). **Size:** 32.5 x 11.5 x 3.5 inches.

Power: 9 to 12 volts AC or DC, at .5 to 3 amps.

Power Supply: Standard—UL listed plug-in wall transformer. 110 volts AC, 60 Hz @ 1 Amp. Power cable included, 3 wire x 25 feet (7.62 meters).

Weight: 20 pounds (9.1 kg) boxed.

Digit Size: 4.5 inch height.

Number of digits: 6 digit x 7 segment (Indicates to 999999)—6 digits x 12 segments with alpha/numeric model.

Display format: Decimal points between ones, tens, and hundreds positions (123.456). Pad with one or two fixed zeros. Switch selectable, or sent from host.

DISTRIBUTED BY:

Intercomp

Totalcomp Scales & Components

13-01 Pollitt Drive Fair Lawn NJ 07410 7-3438
 800-631-0347 201-797-2718
 Fax 888-797-2288 201-797-2287