

# CS Series

## Electronic Crane Scales



- **Lifting-duty hardware**– Makes load connection simple and secure
- **Two Popular Capacities**– 1000 lb (500 kg) and 2000 lb (1000 kg)
- **Sturdy Construction**– Aluminum die-cast case, alloy steel loadcell, hook and shackle
- **Visible LED Display**– Adjustable brightness for any environment
- **Dual Power**– Operate by on-board battery or while connected to charger
- **Remote Control**– Offers increased safety and convenience

VALUE IN  
WEIGHING

# CS Series Electronic Crane Scales

## Features

Salter Brecknell crane scales are versatile, economic solutions for overhead material handling and weighing applications.

**Rechargeable battery**– Operates 20 hours between charges

**Remote control**– Puts all scale functions at your fingertips

**Elongated upper shackle**– Accommodates thick hooks

**Swivel hook with latch**– Makes load connection easy and secure

**Bright LED display**– Has adjustable brightness for any environment

**Dual Units of Measure**– Displays kg or lb

**Accumulator function**– Calculates total weight

## Specifications

**Capacities**– 1000 lb x 0.5 lb (500 kg x 0.2),  
2000 lb x 1 lb (1000 kg x 0.5)

**Accuracy**– +/- 0.3% of reading

**Factory calibration**– 39° latitude optimized

**Dimensions**– 17.0" L x 8.5" W x 5.3" D  
430 mm (L) x 215 mm (W) x 135 mm (D)

**Power**– Rechargeable battery with AC power adapter;  
Remote control requires two AA alkalines

**Display**– 5 digit, 1.2" (30 mm) LED

**Remote Control**– Distance controls for zero, tare, peak, accumulator and power

**Minimum Ultimate Safety Factor**– 400%

**Factory Proof Load**– 125% of capacity

**Typical Battery Life**– 20 hours between charges (room temp)

**Operating Temp**– 14° F to 104° F (-10° C to 40° C)

**Shipping Weight**– 13.5 lb (6.2 kg)

**Carton size**– 12" L x 11" W x 7.5" H  
305 mm (L) x 280 mm (W) x 190 mm (H)



a division of Avery Weigh-Tronix, LLC

## Salter Brecknell Weighing Products

1000 Armstrong Dr., Fairmont, MN 56031  
Toll free: 800-637-0529, Tel: 507-238-8702  
Fax: 507-238-8271  
e-mail: sales@salterbrecknell.com  
www.salterbrecknell.com

